



COST REDUCTIONS








PROXIMITY - ADVICES



PEACE OF MIND - SERVICES

ORIGINAL KUHN PARTS, QUALITY HAS ITS SIGNATURE!

Blades					
Type	Reference Left / Right	Models	Useful information (dim. Lgth x Thickn.)	Corresponding Bolts and Nuts	
Standard blade		52802110	HA 300 / 3000 HA 400 / 4000	Lg 350 mm	Bolt 80061664 Washer 80281600 Nut 80201630
		52503700	HR 180 / 240 / 250 / 300 / 360 / 400 / 450 HRB 20 / 25 / 30 / 40	Lg 320 mm	Bolt 80061675 Washer 80281600 Nut 80201606
		52549530 / 52549430	HR 101 / 102 HRB 101 / 102	Lg 280 mm x 14 mm Dist. between axis: 70 mm Pressed steel blade	Bolt 80061675 Nut 80201662
		52539500 / 52539400	HR 1000 / 1001 / 1002	Lg 300 mm x 16 mm Dist. between axis: 70 mm Forged blade	Bolt 80061682 Nut 80201662
		ECO 525605000 / 52560400		Lg 300 mm x 16 mm Dist. between axis: 70 mm Pressed steel blade	
		FAST-FIT 52625400 / 52625500	HR 103 up to A9999	Lg 305 mm x 18 mm Forged blade	Connecting piece 52596600 Linch pin 50086310
		FAST-FIT 52596510 / 52596410	HR 1003 D / 6003 DR up to A9999 HR 4003 / 5003 DR up to B9999 HR 1002 S	Lg 310 mm x 16 mm Forged blade	
		FAST-FIT 2 K2500071 / K2500081	HRB 102 "S" up to E7671 HRB 103 D / DR	Lg 290 mm x 14 mm Pressed steel blade	
		FAST-FIT 2 K2500090 / K2500100	HR 103 / 1003 D / 6003 DR as from B0001 HR 4003 / 5003 DR as from C0001	Lg 310 mm x 16 mm Pressed steel blade	

Potato blade		52510600	HR 180 / 240 / 250 / 300 / 360 / 400 / 450 HRB 20 / 25 / 30 / 40	Lg 420 mm	Bolt 80061675 Washer 80281600 Nut 80201606
		52552510 / 52552410	HR 101 / 102 HR 1000 / 1001 / 1002 HRB 101 / 102	Lg 350 mm x 14 mm Dist. between axis: 70 mm Pressed steel blade	According to model HR or HRB see Kuhnsets
		FAST-FIT 2 blade K2502040 / K2502050	HR 103 / 1003 D / 6003 DR as from B0001 HR 4003 / 5003 DR as from C0001	Lg 365 mm x 16 mm Pressed steel blade	Connecting piece 52596600 Linch pin 50086310
		FAST-FIT 2 blade K2502060 / K2502070	HRB "102" S as from E7671 HRB 103 D / DR	Lg 340 mm x 14 mm Pressed steel blade	



COST REDUCTIONS










PROXIMITY - ADVICES



PEACE OF MIND - SERVICES

ORIGINAL KUHN PARTS, QUALITY HAS ITS SIGNATURE!

Tines					
Type	Reference Left / right	Models	Useful information (dim. Lgth x Thickn.)	Corresponding Bolts and Nuts	
DURAKUHN blade		52561510 / 52561410	HR 101 / 102 HRB 101 / 102	Lg 280 mm x 14 mm Dist. between axis: 70 mm Pressed steel blade Carbide hardcoated	Bolt 80061675 Nut 80201662
		52556500 / 52556400	HR 1000 / 1001 / 1002	Lg 300 mm x 16 mm Dist. between axis: 70 mm Forged blade Carbide hardcoated	Bolt 80061682 Nut 80201662
		FAST-FIT K2500280 / K2500290	HRB 102 "S" as from E7671 HRB 103 D / DR	Lg 290 mm x 14 mm Pressed steel blade Carbide hardcoated	Connecting piece 52596600 Linch pin 50086310
		FAST-FIT 52597510 / 52597410	HR 1003 D / 6003 DR up to A9999 HR 4003 / 5003 DR up to B9999 HR 1002 S	Lg 310 mm x 16 mm Forged blade Carbide hardcoated	
		FAST-FIT 2 K2502240 / K2502250	HR 103 / 1003 D / 6003 DR as from B0001 HR 4003 / 4503 / 5003 as from C0001	Lg 315 mm x 16 mm Pressed steel blade Carbide hardcoated	
OPTIMIX blade		OPTIMIX 52620500 / 52620400	HR 1003 D / 6003 DR up to A9999 HR 4003 / 5003 DR up to B9999 HR 1002 S	Lg 310 mm x 20 mm Forged blade reversible	Connecting piece 52596600 Linch Pin 50086310
		OPTIMIX 2 K2501120 / K2501130	HR 103 / 1003 D / 6003 DR as from B0001 HR 4003 / 4503 / 5003 as from C0001	Lg 315 mm x 16 mm Pressed steel blade	